



Image may differ from product. See technical specification for details.

# FYC 50 TF

#### Round flanged ball bearing unit with set screw locking, cast iron housing, JIS

These round flanged ball bearing units are compliant with Japanese Industrial Standards (JIS). They consist of an insert bearing, with an extended inner ring and set screw locking, and are suitable for applications where the direction of rotation is constant or alternating. The bearing is mounted in a cast iron housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

- Resist high levels of contamination
- Designed for high temperatures and speeds
- Accommodate relatively heavy loads
- Cost-effective

#### **Overview**

#### Dimensions

Shaft diameter	50 mm
Housing overall width	39.5 mm
Width, total	42.6 mm
Pitch diameter of bolt holes of round and triangle flange type housing	138 mm
Bearing width, total	51.6 mm

## Performance

Basic dynamic load rating	35.1 kN
Basic static load rating	23.2 kN
Limiting speed	4 000 r/min
Note	Limiting speed with shaft tolerance h6

## Properties

Housing type	Flanged
Flanged housing type	Round
Number of bolt holes for fasteners	4
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Cast iron
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, standard
Sealing, unit	Without
Lubricant	Grease
Relubrication hole	With
Grease fitting	With

## Logistics

Product net weight	2.9 kg
eClass code	23-05-16-02
UNSPSC code	31171536

# Technical specification

Compliance with standard	JIS	
Purpose specific	For agricultural applications	
Material, housing	Cast iron	
Sealing, bearing	Seal and flinger on both sides	
Sealing type, bearing	Contact, standard	
Sealing, unit	Without	
Coating	Without	

## Dimensions

d	50 mm	Bore diameter
~		
d <sub>1</sub>	≈ 62.51 mm	Outer diameter of inner ring
A	39.5 mm	Width of housing
A <sub>1</sub>	14 mm	Flange width
A <sub>3</sub>	12 mm	Height of spherical seat centre
В	51.6 mm	Width of inner ring
B <sub>1</sub>	51.6 mm	Overall bearing width
B4	9 mm	Distance from locking device side face to thread centre
D <sub>b</sub>	113.1 mm	External diameter
D <sub>c</sub>	110 mm	Centering diameter
J	138 mm	Pitch diameter of attachment bolts
J <sub>1</sub>	97.6 mm	Distance between attachment bolts
L	165 mm	Outside diameter
Ν	16 mm	Length of attachment bolt hole
S1	32.6 mm	Distance from locking device side face to raceway centre
Т	42.6 mm	Overall width

#### THREADED HOLE

R <sub>G</sub>	1/4-28 UNF	Housing thread for grease fitting
R <sub>1</sub>	22 mm	Axial position of the housing thread

#### GREASE FITTING

D <sub>N</sub>	6.5 mm	Diameter of head sphere of grease fitting
SW <sub>N</sub>	7 mm	Hexagonal key size for the grease fitting
G <sub>N</sub>	1/4-28 SAE-LT	Thread of grease fitting

#### Calculation data

Basic dynamic load rating	С	35.1 kN
Basic static load rating	C <sub>0</sub>	23.2 kN
Fatigue load limit	P <sub>u</sub>	0.98 kN
Limiting speed		4 000 r/min

Limiting speed with shaft tolerance h6

#### Mass

Mass bearing unit

2.85 kg

# Mounting information

Set screw	G <sub>2</sub>	M10x1
Hexagonal key size for set screw		5 mm
Recommended tightening torque for set screw		16.5 N·m
Recommended diameter for attachment bolts, mm	G	14 mm
Recommended diameter for attachment bolts, inch	G	0.5625 in

# Compatible products

### Component

Round flanged housing for insert bearing, cast iron	FYC 510
Insert bearing with set screw locking and extended inner ring	YAR 210-2F

T

# More Information

Product details	Engineering information	interview Tools
Flanged units to ISO standards		Bearing Select
Flanged units to North American standards	Principles of ball bearing units selection and application - Download catalogue (4.9 MB)	Engineering Calculator
Flanged units to Japanese Industrial Standards (JIS)	Principles of selecting mounted bearing solutions	Rolling bearings mounting and dismounting instructions
Flanged units, not standardized (SKF Food Line)	Bearing failure and how to prevent it	
Permissible misalignment		
Locating/non-locating support		
Loads		
Temperature limits		
Permissible speed		
Lubrication		
Mounting and dismounting		
Ordering information		
Designation system		



# Terms of use

By accessing and using this website / app owned and published by AB SKF (publ.) (556007-3495 · Gothenburg) ("SKF"), you agree to the following terms and conditions:

#### Warranty Disclaimer and Limitation of Liability

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app.

Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service.

Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

#### **Third Party Services**

When viewing YouTube content via the SKF website(s) (i.e. using YouTube API Services), you agree to be bound by the YouTube Terms of Service.

#### Copyright

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third parties.

This website /app includes certain images used under license from Shutterstock, Inc.

#### **Trademarks and Patents**

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

#### Changes

SKF reserves the right to make changes or additions to this website / app at any time.